




FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
------	--------------------------------------	----	---------------

ALTERNATIVE INDUKTIVNIM PETLJAMA

	1 1 RA02 ALTERNATIVA ZA INDUKTIVNU PETLJU RA02 Radar Detector - What is an Anti-Smashing Millimeter Wave Radar? - Through the joint optimization design of software and hardware, this product can: - Accurately identify and distinguish the pedestrian, vehicle - And other targets passing through the barrier boom area, - And avoid the phenomena of "smashing the vehicle", "smashing the person" - And "not dropping the barrier boom".	kom	195.00
	1 2 IWAD-400-2 ALTERNATIVA ZA INDUKTIVNU PETLJU IWAD-400-2 Elektro magnetni Detector - Nije potrebno prosecanje asfalta, pogodan za sve vrste saobraćajnica - Rang detekcije $\geq 1.5 \sim 2m$; Horizontalni snop $35^\circ \pm 5^\circ$; vertikalni snop $15^\circ \pm 3^\circ$ - Radna temperatura od $-40^\circ C$ do $+ 85^\circ C$; Stepen zaštite IP67 - 12VDC; 250mA; Isporučuje se bez napajanja - Preporučeno pozicioniranje na visinu 600mm \sim 800mm od osnove saobraćajnice	kom	175.00
	1 3 IDAL-VBR10 ALTERNATIVA ZA INDUKTIVNU PETLJU IDAL-VBR10 Radar Detector - Nije potrebno prosecanje asfalta, pogodan za sve vrste saobraćajnica - Rang detekcije $1 \sim 6m$; za vozila; podesivo $\pm 0.1m$ Za osobe do 1.5m - Ne detektuje, eventualno postavljenu "krutu zavesicu" ispod letve rampe - Horizontalni snop 30° ; vertikalni snop 17° - Radna temperatura od $-40^\circ C$ do $+ 85^\circ C$; Stepen zaštite IP67 - 12VDC; 150mA; Isporučuje se bez napajanja - Preporučeno pozicioniranje na visinu 600mm od osnove saobraćajnice	kom	125.00
	1 4 IDAL-VBR10B ALTERNATIVA ZA INDUKTIVNU PETLJU IDAL-VBR10B Radar Detector - Nije potrebno prosecanje asfalta, pogodan za sve vrste saobraćajnica - Rang detekcije $1 \sim 6m$; za vozila; podesivo $\pm 0.1m$ Za osobe do 1.5m - Horizontalni snop 30° ; vertikalni snop 17° - Radna temperatura od $-40^\circ C$ do $+ 85^\circ C$; Stepen zaštite IP67 - 12VDC; 150mA; Isporučuje se bez napajanja - Preporučeno pozicioniranje na visinu 600mm od osnove saobraćajnice	kom	115.00
	1 5 FAJC-DL001 ALTERNATIVA ZA INDUKTIVNU PETLJU FAJC-DL001 Radar Detector 12VDC - Nije potrebno prosecanje asfalta, pogodan za sve vrste saobraćajnica - Detektuje i vozila i ljude i ISTOVREMENO RAZLIKUJE vozila, odnosno ljude - Rang detekcije $0.1m \sim 3.9m$; Korak: $0.1m$; Snop ide po visini: 54° ; po Širini: 28° - 12VDC; 150mA; Isporučuje se bez napajanja - Preporučeno pozicioniranje na visinu 600mm \sim 760mm od osnove saobraćajnice	kom	245.00
	1 7 FAJC-DL002 DALJINAC ("DE-BUGGER") - Služi za kontrolu i podešavanje FAJC-DL001	kom	195.00

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
------	--------------------------------------	----	---------------

MIKRO-TALASNI DETEKTOR KRETANJA VOZILA I LJUDI

	<p>2 1 IDAL-VMD10-B</p> <p>MIKRO-TALASNI SENZOR KRETANJA DETEKTUJE LJUDE I VOZILA BLACK</p> <ul style="list-style-type: none"> - Microwave Motion Sensor for Automatic Door Opener MIN. 5cm/sec - Working Principle: Doppler effect; Center Frequency: 24.125GHz - Maximum Installation Height: Less than 5m; Relay Output: COM NO - Hold Time: 0.5 seconds; Wire Length: 2.5m; Temperature Range: -25°C to +85°C - Housing Material: ABS plastic; Housing Color: black, silver gray - Power Supply Voltage: 12-24V; Dimensions: 120 (L)*80 (W)*52mm (H) 	kom	45.00
	<p>2 2 IDAL-VMD10-S</p> <p>MIKRO-TALASNI SENZOR KRETANJA DETEKTUJE LJUDE I VOZILA SILVER</p> <ul style="list-style-type: none"> - Microwave Motion Sensor for Automatic Door Opener MIN. 5cm/sec - Working Principle: Doppler effect; Center Frequency: 24.125GHz - Maximum Installation Height: Less than 5m; Relay Output: COM NO - Hold Time: 0.5 seconds; Wire Length: 2.5m; Temperature Range: -25°C to +85°C - Housing Material: ABS plastic; Housing Color: black, silver gray - Power Supply Voltage: 12-24V; Dimensions: 120 (L)*80 (W)*52mm (H) 	kom	45.00
	<p>2 3 MA-204</p> <p>MIKRO-TALASNI SENZOR KRETANJA DETEKTUJE LJUDE I VOZILA "ZAVESA"</p> <ul style="list-style-type: none"> - Microwave Motion Sensor for Automatic Door Opener MIN. 5cm/sec - Working Principle: Doppler effect; Center Frequency: 24.125GHz - Maximum Installation Height: Less than 5m; Relay Output: COM NO - Hold Time: 0.5 seconds; Wire Length: 2.5m; Temperature Range: -25°C to +85°C - Housing Material: ABS plastic; Housing Color: black, silver gray - Power Supply Voltage: 12-24V; Dimensions: 120 (L)*80 (W)*52mm (H) 	kom	45.00
	<p>2 4 IDAL-VMD20</p> <p>DETEKTOR (SMER) KRETANJA VOZILA IDAL-VMD20 DETEKTUJE SAMO VOZILA</p> <ul style="list-style-type: none"> - Working Temperature: -40°C to +80°C; Housing Material: ABS - IDEALAN ZA AUTOMATSKA ROLO VRATA NA MAGACINIMA, I INDUSTRIJI ITD. - Power Supply: 12-24VDC; Center Frequency: 24.125GHz; Installation Height: 2.5-5m - Detection Mode: One-way detection / Two-way - Holding Time: 1s; Relay Output: COM NO NC - VIDEO: https://www.youtube.com/watch?v=P8Wscu_3pqc 	kom	195.00