

RFID ČITAČ KARTICA: RAF006

ZA KANCELARIJE, HOTELE ITD.



Proximity Card Access Control System RFID Card Reader

- > Card type: 125KHz or 13.56MHz Card
 - > RAF006EM: 125KHz (WG26 output)
 - > RAF006Mifare: 13.56MHz (WG34 output)
- Proximity card Access Control System RFID Card Reader
Model No.: RAF006 EM, MF

Introduction:

RAF006E: 125KHz Proximity card reader
RAF006M: 13.56MHz Mifare card reader

Features:

- > 125KHz Proximity /13.56MHz Mifare Card Reader
- > Read Range: Up to 10CM(125KHz)/5CM(13.56MHz)
- > 26/34bit Wiegand (default)
- > Easy to install on Metal Door Frame or Mullion
- > External LED Control
- > External Buzzer Control
- > Indoor / Outdoor Operation
- > Solid Epoxy Potted
- > Waterproof IP65
- > Reverse Polarity Protection



+381 11 355 7599
+381 63 598 017
office@aspekt.rs

Model	RF006EM and RF006MF
Read Range	RF006EM: Up to 10CM, RF006MF:Up to 5CM
Reading Time (Card)	≤300ms
Power / Current	DC 6-14V / Max.70mA
Input Port	2ea (External LED Control, External Buzzer Control)
Output Format	26bit/34bit Wiegand (default)
LED Indicator	2 Colour LED Indicators(Red and Green)
Beeper	Yes
Operating Temperature	-20° to +65°C
Operating Humidity	10% to 90% relative humidity non-condensing
Colour	Silver
Material	ABS+PC with texture
Dimension(W x H x T)mm	120X56X18mm
Weight	50g
Index of Protection	IP65



+381 11 355 7599
+381 63 598 017
office@aspekt.rs