

RFID ČITAČ KARTICA: SA6-RX

ZA KANCELARIJE, HOTELE ITD. „WIEGAND“ PLATFORMA (26bit); IP68



NIŽE U ORIGINALU

Metal Wiegand Reader(EM/HID/Mifare)

The SA6-RX reader is an advanced 125KHz & 13.56MHz technology proximity reader. Because of metal case anti-vandal and waterproof, it can be mounted either indoor or outdoor in harsh environment.

Metal Case, anti-vandal; Waterproof, conforms to IP66

Wiegand 26~37 bits output (default: 26bits); Card type: Hid card, EM card & Mifare card

Reading range: 3~8cm; External LED Control & External Buzzer Control

Product Parameter	Parameter Description
S4A Model	S6-RX
Product Name	Metal RFID Reader (E/H/Mifare)
Operating Voltage	9~24V DC
Frequency	125KHz & 13.56MHz
Card Type	125KHz - EM & Hid Card; 13.56MHz - Mifare Card (ISO 14443A Compatible)
Reading Distance	3~8 CM
Output Format	Wiegand 26 bits (26~37 bits available upon request)
Operating Temperature	-40 oC ~ 60 oC (-40 oF ~ 140 oF)
Standby Current	< 25mA
Operating Humidity	10%~98% RH
Index of Protection	IP66
Dimensions	L103 x W48 x H19 (mm)
Unit Weight	0.25KG
Standard Package	40PCS/carton
Carton Weight	10.8KG
Carton Size	47*30*19(cm)



+381 11 355 7599
 +381 63 598 017
 office@aspekt.rs

KRAJ