



# SAMOSTALAN KONTROLER

PART No: Sboard-BT

NA KOJI SE MOŽE POVEZATI BILO KOJA „WIEGAND“ PERIFERIJA  
ODNOSNO, RFID ČITAČ, SKENER OTISKA PRSTA, BARCODE SKENER ITD.  
APP download is available for Android only; APP name: Ksmart



## NIŽE, U ORIGINALU

Bluetooth Mini Door Access Controller  
Relay: NO NC COM  
User Capacity: 1000users  
Working Voltage: 9-24V  
Support Wiegand 26-37bits output  
APP download is available for Android only  
APP name: Ksmart

User Capacity	1,000
Operating Voltage	9~24V DC
Idle Current	< 20mA
Relay	One (NO, NC, Common)
Adjustable Relay Output Time	0~99 Seconds (5 seconds default)
Lock Output Load	2 Amp Maximum
<b>Wiegand Interface</b>	
Input	Wiegand 26~37 bits
Output	Wiegand 26~37 bits (for user transfer)
Environment	Indoor
Operating Humidity	0 ~ 90%RH
Physical	ABS Shell
Colour	Black
Dimensions	6.5L x 5.4W x 1.9H (cm)
Unit Weight	40g
Shipping Weight	100g



+381 11 355 7599  
+381 63 598 017  
office@aspekt.rs