

PROIZVOD: aButton (EM/MF)

RFID ČITAČ KARTICA, imamo verziju 125.00KHz, ali i verziji 13.56MHz

Obe verzije za WIEGAN konekciju, ali imamo iste i kao SAMOSTALNE (Sboard)

- Montaža istog na zid, štok vrata itd. Potrebna dva samoresca.



NIŽE U ORIGINALU

Model No.: aButton EM, MF

aButton RFID embedded reader is designed for using in the network and standalone access control.

aButton embedded reader supports 125KHz or 13.56MHz keys and connects to the controllers via Wiegand-26/34 protocol.

Model No.	iButton EM	iButton MF
Purpose	ACS reader	
Operating frequency	125KHz	13.56 MHz
Key types	RFID (Proximity)	
Reader standard	TK4100	M1, Mifare Classic 1K, Mifare Classic 4K,
Reader protocol	Wiegand-26, Wiegand-34	
RFID reading range (cm)	0-3	
Keypad	No	
Anti-vandal case	Yes	
Waterproof and dustproof case	Yes	
Keys copying protection	Yes	
Current consumption (mA)	35mA	
Visual indication	1 x Red LED	
External control of LEDs and buzzer	No	
Operating temperature (°C)	-30...+40	
Case material	Polyamide	
Dimensions (mm)	RFID Reader D25 x 22mm; Housing Ø 45mm	

office@aspekt.rs

KRAJ