

14-Apr-17

**ADT5515**

RFID Čitač Kartica

Za ekstremno teške uslove rada**METAL OUTDOOR ACCESS CONTROL READER**


- ◆ Read range 3~15cm for proximity card or Mifare card
- ◆ with Double color LED and Buzzer
- ◆ Suitable for all kinds of access control system

- ◆ Voltage: DC 5~16V; Current ≤100mA
- ◆ Ambient Temperature: -45°C~75°C
- ◆ Reading Range: 5~15CM
- ◆ Output Format: Wiegand 26 (default) / 34,
- ◆ Card Type: EM, or Mifare, or HID, or NFC
- ◆ Communication Distance: WG≤100m
- ◆ Dimension: 120*80*25mm
- ◆ Weight: 0.54kg



RFID Card Type	EM-ID 125kHz, or Mifare I 13.56MHz
Standard Functions	Buzzer, Double color LED
Output Port	Wiegand 26 (default) / WG34, Options: RS485/232
Reading Time (Card)	≤300ms
Color	Metal, Black
Power / Current	DC5~16V
Material	Metal, water resistant IP65, Shockproof, Anti-vandal
Current	≤100mA
Index of Protection	IP65
Working temperature	-45°C~75°C
Reading Range	5~15CM
Size	120*80*25mm
Weight	0.54kg

Distributer:



ASPEKT System Integration d.o.o.
Požeška br. 67a, 11000 Belgrade, Serbia
Phone: +381 11 3557 599
Mobile: +381 63 598 033
office@aspekt.rs