

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
------	--------------------------------------	----	---------------

**DATA TERMINAL ZA EVIDENCIJU I KONTROLU PRISTUPA - KARTICA**



1	1	VAP30	kom	375.00
---	---	-------	-----	--------

VAP30 | Data Terminal | RFID Kartica | TCP/IP  
 ST Microelectronics® 32-Bit High Speed CPU, Stable and reliable.  
 20000 Cards, 200,000 Records, Backlight Keypad, Door Open Sensor, RS485, USB Device, TCP/IP, Wiegand In/Out, Direct Lock Control, Group, Time Zone, Scheduled Bell, Doorbell & Relay Out, Tamper Alarm, Card+ID, ID+PW, PW+Card, IP53, Standard POE Opcija | Citac kartica | Mifare 1K



1	2	C2C Pro	kom	395.00
---	---	---------	-----	--------

C2C Pro | Data Terminal | RFID Kartica & Otisak Prsta | TCP/IP  
 - Dual Cord 1.0G HZ high speed processor, 3.5" TFT LCD display,  
 - Touch on active fingerprint sensor; 10,000 cards, 100,000 Records,  
 - 1 relay for bell and connecting to Access Control system,  
 - 1 RS485 WG out for printing. TCP/IP, WiFi, USB Host, Power Over DC12V/1A,  
 - Webserver, ID+PW, FP, Card, ID+FP, ID+PW, PW+Card, FP+Card, FP+  
 - Default RFID Module EM; Option: Mifare

**DATA TERMINAL ZA EVIDENCIJU I KONTROLU PRISTUPA - KARTICA & OTISAK**



2	1	C2Pro	kom	545.00
---	---	-------	-----	--------

C2Pro | Data Terminal | RFID Kartica & Otisak Prsta | TCP/IP  
 - Dual Cord 1.0G HZ high speed processor, 3.5" TFT LCD display,  
 - Touch on active fingerprint sensor; 10,000 Fingerprints, 100,000 Records,  
 - 1 relay for bell and connecting to Access Control system,  
 - 1 RS485 WG out for printing. TCP/IP, WiFi, USB Host, Power Over DC12V/1A,  
 - Webserver, ID+PW, FP, Card, ID+FP, ID+PW, PW+Card, FP+Card, FP+PW;  
 - Default RFID Module EM; Option: Mifare



2	2	EAP300 Pro	kom	595.00
---	---	------------	-----	--------

EAP300 Pro | DATA TERMINAL - SKENER OTISKA PRSTA & RFID Čitač kartica (ID)  
 - 1Ghz Linux Based High Speed CPU, Touch on active fingerprint sensor  
 - 3,000 Fingerprints, 100,000 Records, Linux, 3.2" TFT LCD, Display Fingerprint  
 - Employee Self-Service Record Inquiry; RS485, USB Host and Mini USB, TCP/IP, Webserver  
 - FP, Card, ID+FP, ID+PW, PW+Card, FP+Card, FP+PW; Option: FRID Čitač Kartica (IC)  
 - Default RFID Module EM; Option: Mifare


**BIOMETRIJSKA OPREMA - SPOLJNA PRIMENA**





3	1	AM5-Pro	kom	445.00
---	---	---------	-----	--------

AM5-Pro | DATA TERMINAL - SKENER OTISKA PRSTA & RFID Čitač kartica | TCP/IP; Wiegand 26  
 - The metal casing, with IP65 water-proof design | -30°C to 60°C  
 - User Capacity 5000; Log Capacity: 50,000; Verification Speed: < 0.5s(1:N)  
 - Wiegand Out, Direct Lock Control, Tamper alarm output  
 - Size(WxHxD): 50 x 124 x 34.5 mm | DC 12V; 150mA | CE; FCC; RoHS  
 - Default RFID Module EM; Option: Mifare


**BIOMETRIJSKA OPREMA - SPOLJNA PRIMENA - IZRAZITO ROBUSNA OPREMA**

FOTO	OPIS PROIZVODA / PRODUCT DESCRIPTION	JM	VP CENA (EUR)
	4 1 TA60 Pro TA60 Pro   DATA TERMINAL - SKENER OTISKA PRSTA & RFID Čitač kartica & Šifra   Webservice - 1Ghz Linux Based High Speed CPU, Stable and reliable. 2.8" Color TFT-LCD Screen - 3,000 Fingerprints, 100,000 Records, Voice Prompt, RS485, USB Device, - TCP/IP, POE (IEEE802.3af), Wiegand In & Out, Direct Lock Control, Group, Time Zone, - Scheduled Bell, Doorbell & 2 Relay Out, Tamper Alarm, Door Open Sensor, - FP,Card,ID+FP,ID+PW,PW+Card,FP+Card,FP+PW; IP5; -30°C to 60°C - Default RFID Module EM; Option: Mifare	kom	545.00


### DESK-TOP PRIMENA

	5 1 U-Bio U-Bio   Deask Top   Fingerprint reader   USB	kom	155.00
	5 2 M-Bio M-Bio   Deask Top DATA TERMINAL   Fingerprint reader & RFIF Reader ( EM&Mifare 2 in 1 ) - Namenjen desk top sistemu Evidencije i kontrole pristupa; Korisnika:3,000 - Evidencija pristupa, USB; za Kontrolu pristupa dodat SC011	kom	245.00

### BIOMETRIJSKA OPREMA - VERIFIKACIJA GEOMETRIJE LICA

	7 1 FacePass 7 Pro Data Terminal (unutrasnja primena)   Face Recognition & RFID & Rec. (3,000/3,000/100,000) - TCP/IP, RS485, USB Host, WiFi; 3.2" HD TFT Touch Screen   -20 °C~ 60 °C - Relay Output, Wiegand26/34 Input and output, magnetic, etc. - Door Sensor, Switch, Doorbell; Software: Crosschex Standard - Dimensions(W x H x D): 124*155*92mm	kom	495.00
--	---	-----	--------

### ACC. KONTROLERI

	8 1 SC011 SC011   Samostalan ACC. Kontroler   za 1 x Weigand periferiju i 1 x EXIT Taster	kom	55.00
--	--	-----	-------