

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

**ACC. KONTROLERI - NAJVIŠI STEPEN SIGURNOSTI - PROFI OPREMA**

	1 1 AE01 ACC. Kontroler za JEDNA vrata   za DVE wiegand (26, 34, 37) periferije (RFID čitača,...) - TCP/IP   Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za jedan Exit taster, za jedan senzor vrata; za jedan PP alarm - IZLAZI (relay): za jedna vrata; za jednu sirenu	kom	145.00
	1 2 AE02 ACC. Kontroler za DVOJA vrata   za ČETIRI wiegand (26, 34, 37) periferije (RFID čitača,...) - TCP/IP   Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za dva Exit tastera, za dva senzora vrata; za dva PP alarma - IZLAZI (relay): za dvoja vrata; za dve sirene	kom	195.00
	1 4 AE04 ACC. Kontroler za ČETVORA vrata   za ČETIRI wiegand (26, 34, 37) periferije (RFID čitača,...) - TCP/IP   Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za četiri Exit tastera, za četiri senzora vrata; za dva PP alarma - IZLAZI (relay): za četvora vrata; za dve sirene	kom	225.00
	1 5 AE04D ACC. Kontroler za ČETVORA vrata   OSAM x wiegand (26, 34, 37) periferija (RFID čitača,...) - RS485 za OSAM periferija (RFID čitača, bar code skenera, itd) - TCP/IP   Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za četiri Exit tastera, za četiri senzora vrata; za dva PP alarma - IZLAZI (relay): za četvora vrata; za dve sirene	kom	275.00
	1 6 MAY104T LINUX   ACC. Kontroler za ČETVORA VRATA   OSAM PERIFERIJA (RFID ČITAČA, ILI ...) - PRERIFERIJE MAX. OSAM wiegand (26, 34, 37) PERIFERIJA (RFID čitača,...), ILI - PRERIFERIJE MAX. OSAM RS485 PERIFERIJA (RFID čitača, bar code skenera, itd) - TCP/IP   Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za četiri Exit tastera, za četiri senzora vrata; za dva PP alarma - IZLAZI (relay): za četvora vrata; za dve sirene	kom	295.00
	1 7 AE05 Acc. Kontroler   Lift, Pretinci, ...   32 x Relay: 2xWiegand Citac; 32 x senzor vrata; 1 x PP alarm - Izlazi (relay): 32 x vrata; 2 x (PP Sirena&Svetlo)   bez kutije i napajanja   - TCP/IP - Web Server, opcija RS485 (do max. 254 Acc. Kontroler) - ID 120,000; Rec. 200,000	kom	345.00

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

### RFID ČITAČI KARTICA - WIEGAND PLATFORMA & SAMOSTALNI

	2 37 AEM1000-125KHz	kom	30.00
RFID Čitač Kartica   EM (125KHz)   wiegand   reading distance : 30 ~ 120mm   - Max. rastojanje od Acc. Kontrolera < 150m   -25°C ~ 70°C   - Unutrasnja (spoljna natkrivena) primena   LED (blue - green)   - LOGO can be customerized			
	2 38 AEM1000-13.56MHz	kom	35.00
RFID Čitač Kartica   M1 (13.56MHz)   wiegand   reading distance : 30 ~ 120mm   - Max. rastojanje od Acc. Kontrolera < 150m   -25°C ~ 70°C   - Unutrasnja (spoljna natkrivena) primena   LED (blue - green)   - Logo: "ASPEKT" (po zahtevi možemo dodati i logo kupca, za kol. +50kom)			
	2 39 AHID-1000	kom	70.00
RFID Čitač Kartica   HID   wiegand   Reading HID card reading distance : 10--15CM - LED status: after powering, blue, and swipe card, change to Green - LOGO can be customerized			
	2 40 RA-128	kom	55.00
RFID Citac Kartica   EM, ili M1   Wiegand 26, 34   rang: 3 ~ 12cm   - rastojanje od Acc. < 150m   -20°C ~ 55°C   Spoljna primena   buzzer - Metalno kuciste, vodo-otporno   DC12V ~ 15V, bez napajanja			
	2 41 ADT5515	kom	65.00
RFID Citac Kartica   EM: 125KHz, opcije M1 13.56MHz, HID, NFC   rang: 3 ~ 7cm - Wiegand 26/34, rastojanje od Acc. < 100m   Opcija RS485/RS232, od Acc. < 1200m - IP65, -45°C ~ 70°C   metal case; water proof; Shockproof; anti vandal - Namenjen za izrazito teške uslove rada			
	2 45 ACAM211B-EM	kom	55.00
Serija GB   RFID Citac Kartica   EM 125KHz   Wiegand & STAND ALONE   + ulaz za eksterni citac - Šifратор "touch metal keypad"   rang: 3 ~ 12cm   rastojanje od Acc. < 150m   - Spoljna primena   buzzer   metalno kuciste, vodo-otporno - DC12V ~ 15V; ID Card, Users 2000   -20°C ~ 55°C			
	2 46 AMA-1	kom	75.00
RFID Citac Kartica   EM, ili Mifare   Wiegand & STAND ALONE   + ulaz za eksterni citac - Šifратор "touch keypad"   rang: 3 ~ 12cm   rastojanje od Acc. < 150m   -20°C ~ 55°C - Spoljna primena (natkriveno)   buzzer   metalno kuciste, vodo-otporno - DC12V ~ 15V; ID Card, Users 2000			







FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	2 48 U2 RFID Citac Kartica   EM, ili Mifare   Wiegand 26/34 input & output & STAND ALONE - METALNO KUČIŠTE; vodo-otporno IP68; anti vandal   LED, buzzer - Rang: 3 ~ 12cm   rastojanje od Acc. < 150m   -35°C ~ 60°C - DC12V; ID Card, Users 2000   Certification: RoHs, FCC, CE	kom	75.00
	2 50 DT5522ID RFID Citac Kartica   EM, ili M1   Tastatura & LCD Displej   RS485   rang: 3 ~ 12cm   - Rastojanje < 1,200m   -20°C ~ 55°C   Unutrasnja primena   buzzer   DC12V ~ 15V !	kom	125.00
	2 52 AF6-USB Fingerprint Scanner   RFID (EM) REader   out door   metal case; water proof; anti vandal - USB; RS232; RS485; wiegand 26, 34   stand alone   Fingers 1000   ID Card 1000 - 2xFinger; 1xCard   Card, ili FP   Card + FP	kom	135.00
	2 55 AS600-EM Citac Kartica   EM (125MHz)   Wiegand & STAND ALONE   Šifратор "metal keypad"   IP68 - rang: 3 ~ 12cm   rastojanje od Acc. < 150m   -45°C ~ 60°C   Spoljna primena; buzzer - metalno kućiste, vodo-otporno; anti-vandal   DC12V ~ 15V - U "stand alone" režimu kapacitet 2,000 (RFID Kartica, PWD različitih) - Na "wiegand"-u kapacitet 30,000 (RFID Kartica, PWD različitih)	kom	70.00
	2 56 AS600-MIFARE Citac Kartica   MIFARE   Wiegand & STAND ALONE   Šifратор "metal keypad"   IP68 - rang: 3 ~ 12cm   rastojanje od Acc. < 150m   -45°C ~ 60°C   Spoljna primena; buzzer - metalno kućiste, vodo-otporno; anti-vandal   DC12V ~ 15V - U "stand alone" režimu kapacitet 2,000 (RFID Kartica, PWD različitih) - Na "wiegand"-u kapacitet 30,000 (RFID Kartica, PWD različitih)	kom	70.00
	2 57 AHCC760-MSR Citac Kartica   Mag. Stripe   Wiegand26   "swipe" - kontakt - Rastojanje od Acc. < 100m   -10°C ~ 70°C   Metalno kuciste	kom	125.00

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

**RFID ČITAČI KARTICA - WiFi; TCP/IP; WIEGAND**

4 88

YAFBAK-8100

kom

95.00

SAMOSTALNI RFID ČITAČ-RFID MIFARE-"TOUCH" TASTATURA | IP66 | SERIJA 4000

- Opcije otključavanja: autorizovana ŠIFRA i/ili RFID Kartica i/ili korisnički mobilni telefon
- Upravljanje sistemom: "master" mobilni telefon (ANDROID, IOS, Bluetooth 4.0)
- Kapacitete: 20.000 RFID Kartica | ŠIFRA i/ili Korisničkih mob. Telefona: ne ograničen



4 89

YAFBA-8100

kom

90.00

SAMOSTALNI RFID ČITAČ-RFID MIFARE-ZVONCE "TOUCH" TASTER | IP66 | SERIJA 4000

- Opcije otključavanja: autorizovana RFID Kartica i/ili korisnički mobilni telefon
- Upravljanje sistemom: "master" mobilni telefon (ANDROID, IOS, Bluetooth 4.0)
- Kapacitete: 20.000 RFID Kartica | Korisničkih mob. Telefona: ne ograničen
- Napajanje 12VDC; potrošnja 50mA; materijal: tamperisano staklo, aluminijumski okvir

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

**DATA TERMINALI - RFID & TASTATURA**



7	102	ASC103/ASC403	kom	185.00
---	-----	---------------	-----	--------

DATA TERMINAL | RFID (125KHz) TA+ACC | EVIDENCIJA I KONTROLA PRISTUPA  
 - TCP/IP, USB host, RS232/485; 30,000 user; 50,000 records; anti-pass back; webserver  
 - 50 x Time Zone, 5 x Grouping, 10 x Combination | Wiegand In/Out  
 - Audio Visual Indicator: Red LED (Access denied) / Green LED (Access granted)  
 - With Audible Beep; Dim: 159\*136\*40mm; 0°C ~ 45°C; RH 20% ~ 80%  
 - Opcije: Mifare, HID,  
 - CE, FCC, RoHS Sertifikati



7	103	ACAM103	kom	195.00
---	-----	---------	-----	--------

DATA TERMINAL | RFID (13.56GHz) TA+ACC | EVIDENCIJA I KONTROLA PRISTUPA  
 - TCP/IP, USB host, RS232/485; 30,000 user; 50,000 records; anti-pass back; webserver  
 - 50 x Time Zone, 5 x Grouping, 10 x Combination | Wiegand In/Out  
 - Audio Visual Indicator: Red LED (Access denied) / Green LED (Access granted)  
 - With Audible Beep; Dim: 159\*136\*40mm; 0°C ~ 45°C; RH 20% ~ 80%  
 - Opcije: Mifare, HID,  
 - CE, FCC, RoHS Sertifikati



7	108	AE01-NET-B-K	kom	95.00
---	-----	--------------	-----	-------

DATA TERMINAL | AOP | RFID Čitač Kartica & TASTATURA & ZVONCE | ETHERNET (TCP/IP)  
 - ID Card holder: 21000, Logs | 50,000 Alarm; 60,000 Events  
 - External Card reader (1) IN on wiegand; EXIT button (1) IN; Fire alarm (1) IN  
 - Door sensor (1) IN; Door lock NO/NC (1) OUT; Zvonce (1) NC OUT







7	109	AE01-NET-B-LCD	kom	100.00
---	-----	----------------	-----	--------

DATA TERMINAL | AOP | RFID Čitač Kartica & TASTATURA & ZVONCE | LCD | ETHERNET (TCP/IP)  
 - ID Card holder: 21000, Logs | 50,000 Alarm; 60,000 Events  
 - External Card reader (1) IN on wiegand; EXIT button (1) IN; Fire alarm (1) IN  
 - Door sensor (1) IN; Door lock NO/NC (1) OUT; Zvonce (1) NC OUT

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

**RFID (UHF) ČITAČI KARTICA - DESK TOP**

	8 111 ADT5512- USB Citac Kartica RFID   EM: 125KHz   USB   rang: 3 ~ 15cm	kom	33.00
	8 112 ADT5512-USB -MF Citac Kartica RFID   Mifare: 13.56KHz   USB   rang: 3 ~ 15cm	kom	39.00
	8 113 ADT5512-HID-R HID USB READER   Interface: USB Read HID 26,34,35,36,37,40bits (125khz)	kom	125.00
	8 116 ADT5512-HID HID PROGRAMER   Interface: USB Providing many interface functions Program - HID 26,34,35,36,37,40bits   compatible cards	kom	750.00
	8 117 AER300L NFC card issuer, send NFC UID card no. we can set card output no. format, - working with NFC mobile phone.	kom	95.00
	8 118 AER302 NFC card writer, can change Ultralight card to NFC card, provide SDK, and samples, - can identify different types of card, read and write NFC tags, - Elink make website linking automatically, - Eflow makes text input, Epurse can realize consumption, - and can save consumption records.also write person and things info. - can modify sector PSW, and initialize whole card.	kom	125.00

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
<b>KONVERTER</b>			
	9 122 RS232-WG KONVERTER   RS232 na Wiegand 26, 34	kom	45.00
	9 131 APS26 KONVERTER   PS2 na Wiegand 26, 34 - PS2 to Wiegand 26bit or Wiegand 34bit	kom	70.00
	9 132 AWST-RS2322WG KONVERTER   RS232 na Wiegand 26, 34   - converter support double-way transmission; Wiegand 26bit or Wiegand 34bit to RS232 - RS232 to Wiegand 26bit or Wiegand 34bit	kom	45.00
	9 133 AWST-WG2USB KONVERTER   USB na Wiegand 26, 34   - converter support double-way transmission; Wiegand 26bit or Wiegand 34bit to USB - USB to Wiegand 26bit or Wiegand 34bit	kom	75.00